



BMG28BL-1



Generator Model	Engine brand	Engine Model	Alternator brand	Alternator model	Controller
BMG28BL-1	Baudouin	4M06G35/5	Nidec Leroy Somer	LSAP 42.3 F	DEIF SGC 120/420
Prime Power KVA/KW	Standby Power KVA/KW	Power Factor/ Phase	Fuel Tank	Net weight	Dimensions
25 / 25	27.5 / 27.5	1.0/ 1 phase	77	960	2350*850*1290

High quality industrial waterproof canopy ensures low noise level 68 DBA (at 7m, 0% load)

Standby: Standby power standby duty, operation under variable load, without overload.

Prime Power: Prime Power Continuous duty operation, under variable load, 10% overloads permissible 1/12hr.



ENGINE TECHNICAL DATA

ENGINE MODEL: BAUDOUIN 4M06G35/5

Speed	Gross Engine Output		Net Engine Output	
	PRP	ESP	PRP	ESP
RPM	kW	kW	kW	kW
1500	30	33	29	32

- 1) All ratings are based on operating conditions under ISO 8528-1, ISO 3046, DIN6271. Performance tolerance of $\pm 5\%$.
- 2) Test conditions: 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.
- 3) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.

BASIC DATA

Engine Model	4M06G35/5
No. of Cylinders/Valves	4/8
Bore x Stroke (mm)	89 x 92
Displacement (L)	2.3
Governor	Electronic
Aspiration	Turbocharged
Compression Ratio	17.5:1
Piston Speed (m/s)	4.6
Air Intake Flow @ ESP (m ³ /min)	1.98
Exhaust Flow @ ESP (m ³ /min)	6.48
Weight (Kg)	272
Cooling fan airflow (m ³ /min)	48



FUEL CONSUMPTION (L/h)

100% load ESP	8.4
100% load PRP	7.6
75% load PRP	5.7
50% load PRP	4

LUBRICATION SYSTEM

Oil pressure in normal condition idle speed (Bar)	>=1
Lowest oil pressure alarm (shutdown) (Bar)	1
Max. oil temperature permitted in oil pan (°C)	115
Total system capacity (including filters) (L)	11.5

COOLING SYSTEM

Coolant alarm (shutdown) temperature (°C)	105
Thermostat adjusting temperature (°C)	72/82
Coolant capacity-engine only(L)	5

FUEL SYSTEM

Max. restriction at fuel pump inlet (Bar)	0.5
Fuel supply flow (L/hr)	40.2
Max. fuel return restriction (Bar)	0.5
Max. fuel inlet temperature (°C)	50

ELECTRIC SYSTEM

Battery charger current (A)	55
Starter power (kW)	3.7

ALTERNATOR TECHNICAL DATA



Brand	NIDEC LEROY SOMER
Model	LSAP 42.3 F
Power	25 kVA
Number of Poles	4
Insulation	Class H
Protection class (according IEC-34-5)	IP23
Exciter system	Self-excited, brushless
Voltage regulator	A.V.R. (Electronic)
Bracket type	Single bearing

GENSET CONTROLLER DEIF SGC 120/420

Control	Auto/Start/Stop Control
	Emergency Stop Pushbutton/ Alarm
Indications	Engine Cool Down Timer
	Warm - up Timer
Warning & Shutdown Alarms	Load Switching Timer
	Engine Cycle Crank
Features	Operating Hours
	3 Phase Generator Voltage Sensing & Monitoring
Warning & Shutdown Alarms	Current Protection & Monitoring
	Power Measurement (kW, kVA, kVAr, kWh, kVAh, pf)
Features	Frequency Monitoring (Hz)
	Oil Pressure/Coolant Temperature/Fuel Level Monitoring
Warning & Shutdown Alarms	Battery Voltage Monitoring (DC)
	Alarm (Acknowledge)
Features	Generator Over/Under Voltage & Frequency
	Crank Disconnect (Failure to Start)
Warning & Shutdown Alarms	Under/Over Speed
	Over Current
Features	Low oil pressure
	High Water Temperature
Warning & Shutdown Alarms	Low Fuel Level
	Low Water Level
Features	IP 65 (if ordered with gasket)
	Basic Scheduler
Warning & Shutdown Alarms	8 - 35V DC Supply
	Digital Inputs(4) - Outputs(4 MPU/ 6 CAN)
Features	Event Log (5 shutdowns)



Disclaimer: In line with continuous product development, we reserve the right to change specifications without notice.

BMGPOWER

MOTEURS Baudouin

INNOVATIVE POWER SOLUTION
Authorized Partner of **MOTEURS Baudouin** In Viet Nam

Head Office: No 31 lane 92, Nguyen Khanh Toan Str,
Cau Giay Dist, Ha Noi, Vietnam.
www.bmgpower.vn

BAUDOIN ENGINES FRANCE

Made in India
www.baudouin.com
www.baudouinpower.vn